



NABCEP's Solar PV Installer Exam is notoriously hard.
Here are 50 practice questions to help you pass.

NABCEP Certification Exam Prep

1. NEC section _____ shows the requirements for working spaces around live electrical equipment?

NABCP Certification Exam Prep

1. Answer:

110.26

NABCEP Certification Exam Prep

2. What is the maximum latitude at which the sun can achieve a 90° altitude angle?
- a. 30.45°
 - b. 23.45°
 - c. 18.45°
 - d. 40.45°

NABCEP Certification Exam Prep

2. Answer:

b. Approx. 23.45° north and south of the equator, but like magnetic declination, the latitude of the Tropics varies over time.

NABCEP Certification Exam Prep

3. If the open circuit voltage of a polycrystalline silicon PV module is 37.0V, the module V_{mp} is 29.9V, the inverter max voltage is 600VDC and its MPPT voltage range is 300 to 480VDC, and the minimum temperature is -24°C . What is the maximum number of modules per source circuit according to the NEC? List the NEC section where the answer is found.

- a. 11
- b. 14
- c. 13
- d. None of the above

NABCEP Certification Exam Prep

3. Answer C:

$$37V \times 1.20 = 44.4V$$

$$600V \text{ max} \div 44.4V = 13.4 \rightarrow 13 \text{ modules}$$

NEC Table 690.7 – 1.20 correction factor


NABCEP Certification Exam Prep

4. A PV array of Suniva 300 Watt modules consists of 3 rows and 10 columns of racked modules mounted in landscape and facing south at latitude 30° . The modules are tilted at 20° . The mounting posts are installed 3 ft. deep. How long must the posts be? Module dimensions are 77.6" x 38.7".

- a. 94.05"
- b. 62.54"
- c. 75.7"
- d. 39.7"

NABCEP Certification Exam Prep

4. Answer



Answer: C

$\text{Sin}(\text{angle}) = \text{opposite} \div \text{hypotenuse}$

$$\text{Sin}(20^\circ) = \text{Height} \div 116.1''$$

$$\text{Height} = \text{sin}(20^\circ) \times 116.1''$$


$$\text{Height} = 0.342 \times 116.1'' = 39.7''$$


$$39.7'' + 36'' = 75.7''$$

for your test with Sea

NABCEP Certification Exam Prep

5. An array located at 30°N latitude consists of two rows racked facing south. Both rows are on a level surface and the height from the ground to the highest point on the module is $39.7''$. Calculate the minimum distance in feet needed between rows so the modules will not be shaded at 9AM on December 21. Use the sun chart provided.





NABCEP Certification Exam Prep

5. Answers:

a. 103.3''

b. 8.6'

c. 9'

d. 5.7'

NABCEP Certification Exam Prep

5. Answer: b

$\text{Tan}(\text{angle}) = \text{opposite} \div \text{adjacent}$ where opposite is array height and adjacent is row-to-row spacing

$$\text{Tan}(21^\circ) = 39.7'' \div \text{Row-to-row}$$

$$\text{Row-to-row} = 39.7'' \div 0.384$$

$$\text{Row-to-row} = 103.4'' \text{ or } 8.6'$$

NABCEP Certification Exam Prep

6. At 43° North latitude on the winter solstice, the solar altitude angle at noon is_____.

- a. 43°
- b. 23.45°
- c. 90°
- d. 70.45°

NABCEP Certification Exam Prep


6. Answer:

d. 23.55°

$$90^{\circ} - 43^{\circ} (\text{latitude}) + (-23.45^{\circ}) = 23.55^{\circ}$$

For the Summer Solstice, the third number is $+23.45^{\circ}\text{C}$, resulting in 70.45° .

For either equinox, the last number is zero.



NABCEP Certification Exam Prep

7. An array is comprised of 22 modules. Each module is 64.5" x 38.7" and weighs 44.1 lbs. The site will experience 50 psf. of uplift force. What is the approximate total uplift on the array?

- a. 48,000 lbs.
- b. 19,000 lbs.
- c. 13,000 lbs.
- d. 16,000 lbs.

NABCEP Certification Exam Prep

7. Answer:

a. 19,000 lbs.

$64.5'' \times 38.7'' \div 144 \text{ sq. in./sq. ft.} = 17.33 \text{ sq. ft.}$

$17.33 \text{ sq. ft.} \times 22 \text{ modules} \times 50 \text{ psf} = 19063 \text{ lbs.}$

NABCEP Certification Exam Prep

8. What is the temperature correction factor if the module correction factor is $-0.335 \text{ } \%/^{\circ}\text{C}$ and the cell temperature is 54°C ?

- a. 0.903
- b. 1.181
- c. 1.097
- d. 0.819

NABCEP Certification Exam Prep

8. Answer:

a. 0.903

$$1 + (-0.00335 \times (54 - 25)) = 0.903$$

NABCEP Certification Exam Prep

9. A module has dimensions of 64.5" x 38.7" and is in a landscape orientation on a flat roof. The position of the sun at 9am on Dec 21 is 11° elevation and 130° azimuth. What is the maximum tilt angle the modules can have so that there is no inter-row shading. A 2 foot walkway is required between adjacent rows?

- a. 10°
- b. 15°
- c. 20°
- d. 25°

NABCEP Certification Exam Prep

9. Answer:

a. 10° is the closest to 10.8°

Module width x SIN(tilt angle) = module height

Module height x COS(azimuth angle) ÷ TAN(elevation angle) =
minimum row spacing

The azimuth angle is $180 - 130 = 50^\circ$

The height is $24'' \times \text{TAN}(11) \div \text{COS}(50) = 7.26''$

$\text{SIN}^{-1}(7.26'' \div 38.7'') = 10.8^\circ$ tilt angle

NABCEP Certification Exam Prep

10. Where no overcurrent protection is provided for the PV dc circuit, an assumed overcurrent device rated at the PV circuit I_{sc} is used to size the equipment grounding conductor in accordance with NEC ____.

- a. Article 250.122
- b. Article 250.66
- c. Table 250.122
- d. Table 250.66

NABCEP Certification Exam Prep

10. Answer:

c. Table 250.122

NEC Article 690.45(A) refers to Table 250.122

NABCEP Certification Exam Prep

11. There are to be two critical loads on a PV system. Your analysis shows that one uses 1900 Wh/day and operates for 6 hrs. per day and the other uses 1200 Wh/day and operates for 3.5 hrs. What is the weighted average operating time?

- a. 4.9 hrs./day
- b. 5 hrs./day
- c. 9.5 hrs./day
- d. 5.3 hrs./day

NABCEP Certification Exam Prep

11. Answer: b. 5 hrs./day

$$\frac{(1900 \text{ Wh/day} \times 6 \text{ hrs.}) + (1200 \text{ Wh/day} \times 3.5 \text{ hrs.})}{(1900 \text{ Wh/day} + 1200 \text{ Wh/day})} = 5 \text{ hrs.}$$

NABCEP Certification Exam Prep

12. What is the combined effect in wattage of the 2 loads in the previous question?

- a. 3500 Watts
- b. 620 Watts
- c. 140 Watts
- d. 1.9 Watts

NABCEP Certification Exam Prep

12. Answer: b 620 Watts

$$\frac{(1900 \text{ Wh/day} + 1200 \text{ Wh/day})}{5.0 \text{ hrs.}} = 620\text{W}$$

NABCEP Certification Exam Prep

13. The critical design month is the worst case scenario where the load and the _____ are used to design the PV system.

- a. Peak demand
- b. Total power demand
- c. Duty cycle
- d. Insolation data

NABCEP Certification Exam Prep

13. Answer: d. Insolation data

NABCEP Certification Exam Prep

14. Active means of charge control is required by the NEC unless the maximum array charge current for 1 hour is less than _____ % of the rated battery capacity measured in amp/hours.

- a. 1
- b. 3
- c. 5
- d. 10

NABCEP Certification Exam Prep

14. Answer: b. 3%

See NEC 690.72

NABCEP Certification Exam Prep

15. When battery temperature is high, temperature compensation _____ the VR set point to minimize the excessive over charging and reduce electrolyte losses.
- a. lowers
 - b. raises
 - c. does not change
 - d. none of the above

NABCEP Certification Exam Prep

15. Answer: a Lowers

NABCEP Certification Exam Prep

16. A 48 volt battery bank is used to provide power for critical loads requiring 7458 Wh/day. Three days of autonomy are required. What is the required capacity of the battery bank?

- a. 155.4 Ah
- b. 466 Ah
- c. 604 Ah
- d. None of the above

NABCEP Certification Exam Prep

16. Answer: b. 466 Ah

$$7458 \text{ Wh} \div 48\text{V} = 155.4 \text{ Ah/day}$$

$$155.4 \text{ Ah/day} \times 3 \text{ days autonomy} = 466 \text{ Ah}$$

NABCEP Certification Exam Prep

17. Critical loads operate for 12 hours. Three days of autonomy are required and the preferred depth of discharge of 50%. What is the average discharge rate?

- a. C/180
- b. C/72
- c. C/36
- d. C/24

NABCEP Certification Exam Prep

17. Answer: b. C/72

12 hrs./day x 3 days autonomy = 36 hrs

36 hrs. ÷ 0.5 DOD = 72 hrs. → C/72

NABCEP Certification Exam Prep

18. A battery bank of 500 Ah is required. The depth of discharge is 50%, the minimum operating temperature is -10°C and the average discharge rate is C/128. According to the manufacturer's specs. this yields a temperature and discharge rate derating factor of approximately 73%. What is the required battery bank capacity?

- a. 250 Ah
- b. 1370 Ah
- c. 684 Ah
- d. 1000 Ah

NABCEP Certification Exam Prep

18. Answer: b. 1370Ah

Given 50% DOD, the battery bank must be:

$$500 \text{ Ah} \div 0.5 = 1000 \text{ Ah}$$

Because 27% of the capacity is lost due to cold temperatures per the manufacturer:

$$1000 \text{ Ah} \div 0.73 = 1369.9 \text{ Ah} \rightarrow 1370 \text{ Ah}$$

NABCEP Certification Exam Prep

19. A battery bank must supply 1200 Ah and will operate at 48V. The battery selected is an 800 Ah battery. How many 6V batteries will be required in this battery bank?

- a. 8
- b. 16
- c. 24
- d. None of the above

NABCEP Certification Exam Prep

19. Answer: b. 16

$48V \text{ bank} \div 6V \text{ battery} = 16$ batteries in series to achieve voltage

$1200 \text{ Ah} \div 800\text{Ah} = 1.5 \rightarrow 2$ parallel strings of batteries

$$8 \times 2 = 16$$

Nothing was mentioned about DOD.

NABCEP Certification Exam Prep

20. A PV system needs to supply 5834 Wh per day. The daily average insolation is 4.8 peak sun hours. The battery system charging efficiency is 0.9. The nominal voltage is 48V. What is the required array current not including any additional deration factors?

- a. 27.9A
- b. 28.1A
- c. 64.8A
- d. 25.3A

NABCEP Certification Exam Prep

20. Answer: b. 28.1A

$$5834 \text{ Wh/day} \div 4.8 \text{ Peak Sun Hours} = 1215.4\text{W}$$

$$1215.4\text{W} \div 0.9 \text{ charging efficiency} = 1350.5\text{W}$$

$$1350.5\text{W} \div 48\text{V} = 28.1\text{A}$$

NABCEP Certification Exam Prep

21. You are an installer called to move a residential two-axis tracker system from Yuma, AZ to Duluth, MN. Before reinstalling the system what should you check?


- a) The system open circuit voltage
- b) The new house branch circuit amperage
- c) The breaker size of the main panel
- d) The insolation difference

NABCEP Certification Exam Prep

21. Answer: a. Check the Voc.

NABCEP Certification Exam Prep

22. For a PV array to directly face the sun at 11 AM solar time on June 21st at 30°N latitude, at what tilt and azimuth angles should the modules be mounted? Use the sun-path chart provided.



NABCEP Certification Exam Prep

22. Answer:

Approximately 14° elevation and 63° E azimuth

$$\text{Elevation} = 90^{\circ} - 76^{\circ} = 14^{\circ}$$

Note: The sum of all angles in any triangle = 180°

NABCEP Certification Exam Prep

23. The purpose of a linear current booster is to:
- a. Keep its output voltage the same as its input voltage and boost the output current to a value larger than the input current.
 - b. Convert a high input voltage and low input current to a lower output voltage and a higher output current.
 - c. Convert a low input voltage and high input current to a higher input voltage and a lower input current.
 - d. Keep its output current the same as its input current and boost the output voltage to a value larger than the input voltage.

NABCEP Certification Exam Prep

23. Answer: b. Convert a high input voltage and low input current to a lower output voltage and a higher output current

NABCEP Certification Exam Prep

24. Where the removal of the utility-interactive inverter or other equipment disconnects the bonding connection between the grounding electrode conductor and the photovoltaic source and/or the photovoltaic output circuit grounded conductor, a ____ shall be installed to maintain the system grounding while the inverter or other equipment is removed.

- a. Grounding-electrode conductor
- b. Fuse
- c. Bonding jumper
- d. Overcurrent device

NABCEP Certification Exam Prep

24. Answer:
c. Bonding jumper

NEC Article 690.49

NABCEP Certification Exam Prep

25. In addition to NEC Article 690, where else in the NEC are over-current devices addressed?

- a. Article 250
- b. Article 300
- c. Article 100
- d. Article 240

NABCEP Certification Exam Prep

25. Answer:
d. Article 240

NABCEP Certification Exam Prep

26. You are inspecting a PV system in Oregon. The array is facing south on a 6/12 pitch roof and the PV equipment is on the east side of the house 60 feet from the combiner. You see an SMA inverter with a #6 GEC run to the ground rod. To the right, is a 30A disconnect with EMT extending to the roof. Inside the disconnect you see two black PV conductors landed onto the terminals. Your inspection of the combiner box on the roof shows two black PV wires. Each one is terminated on a fuse holder and the ground wire is terminated on the ground bus. What type of PV system are you inspecting?

- a. Positive ground system
- b. Bi-polar
- c. Ungrounded
- d. Negative ground system

NABCEP Certification Exam Prep

26. Answer:

c. Ungrounded

NABCEP Certification Exam Prep

27. USE-2 wire must be strapped and secured between modules at intervals no more than:

- a. 6'
- b. 3'
- c. 4.5'
- d. 10'

NABCEP Certification Exam Prep

27. Answer:

c. 4.5'

Installation methods for exterior USE-2 conductors, commonly used in PV arrays, are stated in **NEC 338.10(B)(4)**. This section refers to **Article 334.30** for support methods. Article 334 is entitled Non-Metallic Sheathed Cable (often referred to by the trade name Romex).

The requirements for fastening NM cable are well understood by AHJ. (Field Inspection Guidelines by Bill Brooks)

NABCEP Certification Exam Prep

28. If the uplift force on a system is 1,200 pounds with a safety factor of 1.5, what is the uplift force with a safety factor of 2?

- a. 800 lbs
- b. 1200 lbs
- c. 1400 lbs
- d. 1600 lbs

NABCEP Certification Exam Prep

28. Answer:

d. 1600 lbs

$$1200 \text{ lbs} \div 1.5 = 800 \text{ lbs}$$

$$800 \text{ lbs} \times 2 = 1600 \text{ lbs}$$

NABCEP Certification Exam Prep

29. When GFP is used on an inverter, the grounded and grounding conductors should be:

- a. Grounded: Isolated, grounding: Isolated from case
- b. Grounding: Isolated, grounded: Connected to case
- c. Both: Connected to case
- d. Grounding: Connected to case, Grounded: Bonded to grounding

NABCEP Certification Exam Prep

29. Answer:

d. Grounding: Connected to case, Grounded: Bonded to grounding

NABCEP Certification Exam Prep

30. A customer in New Mexico has a 6000W grid-tied PV system. Every day around noon during the summer, the 25A solar breaker trips. The inverter is on the south side of the house. The conduit run from the inverter to the transition box is 200 ft. The array is facing true south at latitude. What should be done to prevent the breaker from tripping?

- a. Move the inverter out of the sun to lower its internal temperature
- b. Increase the breaker size
- c. Increase the wire size between the transition box and the inverter to compensate for voltage drop
- d. Decrease the tilt of the array to lower production

NABCEP Certification Exam Prep

30. Answer:

b. Increase the breaker size.

$$6000W \div 1.2 = 5000W \text{ inverter}$$

$$5000W \div 240V = 20.8A$$

$$20.8A \times 1.25 = 26.04A$$

A 30 amp breaker was needed for this system

NABCEP Certification Exam Prep

31. You are on a roof in December to check system production compared with the expected production. You know there will be some shading around 3 p.m. In addition to a multi-meter, what tools will you need?

- a. Pathfinder and Temp. gauge
- b. Pathfinder and Irradiance meter
- c. Irradiance meter and temp. gauge
- d. Temp. gauge and inclinometer

NABCEP Certification Exam Prep

31. Answer:

c. Irradiance meter and temp. gauge

NABCEP Certification Exam Prep

32. When checking short-circuit current on a string of modules, what do you do first?

- a. Measure short circuit current
- b. Inspect for shading
- c. Measure voltage
- d. Measure operating current

NABCEP Certification Exam Prep

32. Answer:

d. Measure operating current

You must verify that the circuit is in the open position before you loosen any terminals to which the conductor is attached.

NABCEP Certification Exam Prep

33. When troubleshooting modules, what do you do?
- a. Disconnect all loads to prevent module arcing when unplugged
 - b. Open DC disconnect on the inverter
 - c. Open AC disconnect
 - d. Pull fuses in combiner box

NABCEP Certification Exam Prep

33. Answer:

a. Disconnect all loads to prevent module arcing when unplugged

All are correct: 1. Open the AC disconnects. 2. Open the DC disconnects. 3. Pull fuses in the combiner box.

Taking all these steps ensures that all loads are disconnected. Then it is safe to work on modules.

NABCEP Certification Exam Prep

34. If an inverter is being used in sell mode, the PV charge controller bulk and float voltages and the inverter bulk and float voltages should be set as follows:
- a. Charge controller bulk and float should be higher than bulk and float of inverter
 - b. Charge controller bulk and float should be lower the bulk and float of inverter
 - c. Bulk should be higher than float on the inverter
 - d. Float should be higher than float on the inverter

NABCEP Certification Exam Prep

34. Answer:

- a. Charge controller bulk and float should be higher than bulk and float of inverter

NABCEP Certification Exam Prep

35. At 75°C which wire would be used?

- a. THW-2, XHHW, RHH
- b. THHN, THW, USE
- c. THW, XHHW, THWN
- d. USE-2, RHW-2, THW

NABCEP Certification Exam Prep

35. Answer:

c. THW, XHHW, THWN

NEC 310.15(B)(16)

NABCEP Certification Exam Prep

36. What should be done if USE-2 wires are found to resting against a roof?

- a. Lift them and strap at 3' distances.
- b. Lift them and strap them at 5' distances.
- c. Put them in EMT conduit.
- d. Put them in liquid-tight conduit.

NABCEP Certification Exam Prep

36. Answer:

a. Lift them and strap at 3' distances

NEC 338.10(B) (4).

NABCEP Certification Exam Prep

37. A potential customer wants a PV system. His average monthly usage is 450kWh. He has a southeast facing roof that is 15 degrees off true south with a 30 degree tilt. He receives 4.9 peak sun hours on average per day. He has a 240V split-phase panel with a 200A breaker. What is the maximum inverter output that can be connected to his electrical panel?

- a. 25A
- b. 30A
- c. 32A
- d. 35A

NABCEP Certification Exam Prep

37. Answer:

c. 32A

200A bus bar X 120% = 240A

(NEC 705.12(D)(2))

240A - 200A main breaker = 40A max solar breaker

40A ÷ 125% = 32A

NABCEP Certification Exam Prep

38. You are installing a ground wire to the rebar on a pole mount.

What size rebar must be used?

a. #2

b. #4

c. #6

d. #8

NABCEP Certification Exam Prep

38. Answer:

b. #4

NEC 250.52(A)(3)(1)

Rebar comes in 1/8 in. increments. Rebar is required to be no smaller than 1/2 in.

$$1/8 = 0.125$$

$$0.5 \div 0.125 = 4$$

NABCEP Certification Exam Prep

39. A 55 foot tree will grow 25 feet during the life of the PV system. How far away does a ground mount system need to be? The system is located at 40 degrees latitude, the sun's lowest altitude angle is 14 degrees and the azimuth angle is 41 degrees.

- a. 263'
- b. 280'
- c. 240'
- d. 330'

NABCEP Certification Exam Prep

39. Answer:

d. 330'

$$\frac{55' + 25' \text{ (tree height at leading edge)}}{\text{Tan}(14^\circ)} = 320.8'$$

I did not multiply by the COS (41) because the question does not say that the array is due north of the tree.

NABCEP Certification Exam Prep

40. A weather vane falls onto an array and there is broken glass. The system is still working. What is the main safety concern and how do you handle it?

- a. No concern. Open AC disconnect, remove vane, unplug broken modules and replace them.
- b. Little concern. Open AC disconnect, put on gloves for broken glass, remove vane and unplug modules to be replaced.
- c. Medium concern. Open DC disconnect, remove vane and unplug modules to be replaced.
- d. Vane has high potential. Open DC disconnect, unplug all modules and remove vane with voltage rated gloves.

NABCEP Certification Exam Prep

40. Answer:

- d. Vane has high potential. Open DC disconnect, unplug all modules and remove vane with voltage rated gloves.

NABCEP Certification Exam Prep

41. What is the most important consideration for construction of a ground mount array in a heavy snow area?
- a. Tilt angle
 - b. Distance from ground to bottom of array
 - c. Row-to-row shading
 - d. All of the above

NABCEP Certification Exam Prep

41. Answer:

b. Distance from ground to bottom of array

Incorrect answers:

a, Tilt angle. Typically on a ground-mount the array will be at latitude. Even at latitude -15° in areas where there is lots of snow this angle will allow snow shedding.

b. Row-to-row shading. The question did not mention multiple rows.

c. Could be correct but not the most accurate choice.

NABCEP Certification Exam Prep

42. System drawings call for #10 wire. The system calls for a 50 amp breaker. What size should the wire be?

- a. #10
- b. #8
- c. #12
- d. #6

NABCEP Certification Exam Prep

42. Answer:

b. #8

NEC 240.4(D) (7) Copper #10 limited to a 30A overcurrent device.

NEC Table 310.15(B)(16) in either 75 or 90 degree column shows #8 good for a 50A breaker

NABCEP Certification Exam Prep

43. At what depth should a 1/0 ground wire be buried?
- a. 12"
 - b. 18"
 - c. 30"
 - d. It shouldn't be buried

NABCEP Certification Exam Prep

43. Answer:

c. 30"

A 1/0 ground wire is actually a ground ring, per Article 250.52 (A) (4)

Article 250.53 (F) states that a 30" minimum burial depth for a ground ring is required.

NABCEP Certification Exam Prep

44. An inverter is on the north side of a house and the array is on the south. Where should the DC and AC disconnects be?
- a. The DC disconnect should be close to the array and the AC disconnect should be next to the inverter.
 - b. Both the DC and AC disconnects should be close to the main service.
 - c. The AC disconnect should be close to the array and the DC next to the inverter.
 - d. The DC and AC disconnects should be on either side of the inverter.

NABCEP Certification Exam Prep

44. Answer:

d. The DC and AC disconnects should be on either side of the inverter.

NEC 690.17

Incorrect answers:

a. and c. Neither of these satisfy the “readily accessible” requirement.

b. Since we don’t know from the question that the main service is in an accessible location, stipulating that the disconnects go close to the main service does not by itself satisfy 690.17.

NABCEP Certification Exam Prep

45. At what distance from the junction box must USE-2 wire be secured?

- a. 10"
- b. 12"
- c. 18"
- d. 36"

NABCEP Certification Exam Prep

45. Answer:

b. 12”

NEC 334.30

NABCEP Certification Exam Prep

46. The power loss due to temperature for a silicon module is listed as $-0.5\%/^{\circ}\text{C}$ in the manufacturer's specifications. The manufacturer recommends two array mounting options; one with a $\frac{3}{4}$ " air gap between the module and the roof and one with a 3" air gap. The closer mounting system causes the array to operate 10°C hotter on average throughout the year. Which mounting system will produce the most energy? How much?
- a. $\frac{3}{4}$ " gap by 5%
 - b. 3" gap by 5%
 - c. 3" gap by 10%
 - d. Both will produce the same

NABCEP Certification Exam Prep

46. Answer: b. 3” gap by 5%

NEC Section: Technically none, but Table 310.15(B)(3)(c) serves as a guide.

Solution:

It should be intuitive based on the Table that a 3” gap will be cooler than a 3/4” gap. So answers “a” and “d” can be eliminated. Since the temperature change is 10°C, the larger gap will produce 5% more power:

$$0.5\%/^{\circ}\text{C} \times 10^{\circ}\text{C} = 5\%$$

NABCEP Certification Exam Prep

47. A 7kW PV system using 3 utility interactive inverters listed to UL 1741 is planned for the roof of a duplex. The inverters may be installed on the roof near the PV array if which of the following conditions are met?
- a. All inverters are mounted in a readily accessible location. DC disconnects are at the inverters. AC disconnects are at the point of interconnection with the service equipment. An array wiring plaque is installed at the inverter location.
 - b. Although the inverters are not mounted in a readily accessible location, there is an additional readily accessible AC disconnect for the system. AC and DC disconnects for all 3 inverters are mounted in or near the inverters. A power rating plaque is mounted on each inverter.
 - c. All inverters are mounted where they can be serviced from a service platform. AC and DC disconnects for all 3 inverters are mounted in or near the inverters. There is an additional readily accessible AC disconnect for the system. A power rating plaque is mounted on each inverter.
 - d. Although none of the inverters are mounted in a readily accessible location, there is an additional readily accessible AC disconnect for the system at the service entrance equipment. AC and DC disconnects for each inverter are mounted in or near the inverters. Plaques with a system description showing all power sources are mounted at the inverters and the service equipment.

NABCEP Certification Exam Prep

47. Answer: d. Although none of the inverters are mounted in a readily accessible location, there is an additional readily accessible AC disconnect for the system at the service entrance equipment. AC and DC disconnects for each inverter are mounted in or near the inverters. Plaques with a system description showing all power sources are mounted at the inverters and the service equipment.

Solution

NEC 2011 Article 690.14 (D) (1-4) Utility-interactive inverters mounted in not-readily - accessible-locations.

NEC 2011 Article 690.14 (C)(1) Requirements and location for Disconnecting Means

NEC 2011 Article 705.10 Permanent plaque or directory.

- a. Does not meet 690.14 D 2, 4.
- b. Meets 690.14 D 1- 2, does not meet 4.
- c. Meets 690.14 D 1-2, does not meet 4.
- d. Meets all definitions provided by 690.14(D)(1-4) and 705.70

NABCEP Certification Exam Prep

Use the following system specifications to answer questions 23 and 24.

PV array size: 9kW

Modules: 200W, 39 lbs each

Location: flat roof of a two-story commercial structure

Mounting: 9' x 5', 43 lb aluminum frames holding 3 modules each

Total weight required: 925 lbs per mounting frame

Ballast: 8"x8"x16" concrete blocks, 27 lbs each

NABCEP Certification Exam Prep

48. What is the total number of concrete blocks required to ballast the system?

- a. 765
- b. 29
- c. 435
- d. 514

NABCEP Certification Exam Prep

48. Answer: c. 435

Solution

Number of modules:

$9000 \text{ (System Watts)} \div 200 \text{ (Watts/module)} = 45 \text{ modules}$

$45 \text{ modules} \div 3 \text{ modules/frame} = 15 \text{ frames for the system}$

$43 \text{ lbs./frame} + (3 \times 39 \text{ lbs./module}) = 160 \text{ lbs. (frame \& modules)}$

$925 \text{ lbs. (required weight per frame)} - 160 \text{ lbs.} = 765 \text{ lbs. of ballast}$

$765 \text{ lbs.} \div 27 \text{ lbs. (block weight)} = 28.3 \rightarrow 29 \text{ blocks per frame}$

$15 \text{ (frames required)} \times 29 \text{ (blocks)} = 435 \text{ blocks to ballast the system}$

Note: The early answer “b. 29” is included to catch test takers who are rushing or not fully understanding what has actually been asked.

NABCEP Certification Exam Prep

49. What is the approximate dead load within the system footprint that the roof must withstand?

- a. 7 lbs./sq. ft.
- b. 21 lbs./sq. ft.
- c. 42 lbs./sq. ft.
- d. 63 lbs./sq. ft.

NABCEP Certification Exam Prep

49. Answer: b. 21 lbs./sq. ft.

$$925 \text{ lbs.} \div (9 \text{ ft.} \times 5 \text{ ft.}) = 20.56 \text{ lbs./sq. ft.}$$

NABCEP Certification Exam Prep

50. A utility interactive PV system is installed on a commercial building. The array is roof mounted and operates at 372Vmp with an operating current of 8.56A. When inspecting the source circuit combiner box located next to the array, you observe the following: the ungrounded PV source circuit conductor is black USE-2/RHW-2, the frame grounding conductor is #6 solid Cu, the box is a NEMA4 rated metal box, the PV output conductors leave the (+) and (-) terminal busses and pass into a male EMT adapter secured with a locknut. What is required to bring the combiner box into compliance with the NEC?
- a. A 600VDC 15A fuse with touch-safe fuse holder must be installed on the ungrounded source circuit conductor.
 - b. A grounding bushing must be installed on the EMT adapter.
 - c. The frame grounding conductor must be changed to #8 stranded Cu.
 - d. None of the above.

NABCEP Certification Exam Prep

50. Answer: d. None of the above

Solution

250.97 states that, for circuits of over 250V to ground, the electrical continuity of metal raceways ... shall be ensured by one or more of the methods specified for services in 250.92(B)

250.92(B)(1-4)

NABCEP Certification Exam Prep

50. Notes Part 1:

- a. Could be correct, but the presence or lack thereof of an OCPD was not specifically mentioned and the language reads the ungrounded not one of the ungrounded, etc.

Plus, not all single string circuits need OCP to satisfy Code- see J Wiles To Fuse or Not to Fuse.

- b. To provide a reliable bonding connection, a bonding bushing would be required only if the box had concentric knockouts which are not encountered in NEMA4 boxes unless listed.

NABCEP Certification Exam Prep

50. Notes Part 2:

- c. This choice is a trap. There are instances where the frame ground would need to be increased from #8 to #6, i.e. if it was subject to physical damage. This is meant as a trick for people who think they are positive about the Code but don't bother checking.

This question is important because this issue is seen quite regularly from both novice PV installers and licensed electricians unfamiliar with the Code.